

Features

- High voltage
- Wider temperature range
- RoHS compliant
- Consumer electronic
- Pulse power
- Hold-up power



Items	Characteristics					
Rated Voltage	3V					
Operating Temperature Range	-40 ~+65°C (-40 ~+85°C@2.5V)					
Surge Voltage	3.2V					
Capacitance Range	1~50F					
Capacitance Tolerance (25°C)	-10~+30%					
Temperature Characteristics	The specifications shall be met at category temperature range from -40°C to 65°C	<table border="1"> <tr> <td>Capacitance Change</td><td>Within 30% of the initial value at 25°C</td></tr> <tr> <td>ESR</td><td>Less than 2 times of the initial specified value</td></tr> </table>	Capacitance Change	Within 30% of the initial value at 25°C	ESR	Less than 2 times of the initial specified value
Capacitance Change	Within 30% of the initial value at 25°C					
ESR	Less than 2 times of the initial specified value					
High Temperature Loaded	The specifications shall be met after rated voltage applied at 65°C for 1000 hours	<table border="1"> <tr> <td>Capacitance Change</td><td>Within 30% of the initial value</td></tr> <tr> <td>ESR</td><td>Less than 4 times of the initial specified value</td></tr> </table>	Capacitance Change	Within 30% of the initial value	ESR	Less than 4 times of the initial specified value
Capacitance Change	Within 30% of the initial value					
ESR	Less than 4 times of the initial specified value					
High Temperature Storage	The specifications shall be met after storage at 65°C for 1000 hours	<table border="1"> <tr> <td>Capacitance Change</td><td>Within 30% of the initial value</td></tr> <tr> <td>ESR</td><td>Less than 2 times of the initial specified value</td></tr> </table>	Capacitance Change	Within 30% of the initial value	ESR	Less than 2 times of the initial specified value
Capacitance Change	Within 30% of the initial value					
ESR	Less than 2 times of the initial specified value					
Cycle Life	The specifications shall be met after 500,000 cycles at 25°C, cycle of charge/discharge from V_R to $1/2V_R$	<table border="1"> <tr> <td>Capacitance Change</td><td>Within 30% of the initial value</td></tr> <tr> <td>ESR</td><td>Less than 2 times of the initial specified value</td></tr> </table>	Capacitance Change	Within 30% of the initial value	ESR	Less than 2 times of the initial specified value
Capacitance Change	Within 30% of the initial value					
ESR	Less than 2 times of the initial specified value					

Dimensions

mm

		<table border="1"> <tr> <td>ΦD</td><td>8</td><td>10</td><td>16</td><td>18</td></tr> <tr> <td>p</td><td>3.5</td><td>5.0</td><td>7.5</td><td></td></tr> <tr> <td>Φd</td><td>0.6</td><td>0.6</td><td>0.8</td><td></td></tr> <tr> <td>a</td><td>1.5</td><td></td><td>2.0</td><td></td></tr> </table>	ΦD	8	10	16	18	p	3.5	5.0	7.5		Φd	0.6	0.6	0.8		a	1.5		2.0	
ΦD	8	10	16	18																		
p	3.5	5.0	7.5																			
Φd	0.6	0.6	0.8																			
a	1.5		2.0																			

Standard Ratings for SRE Series

U _R (Surge Voltage) Code	Rated Capacitance 25°C	Impedance		Leakage Current (72hrs)	Size ΦD×L	Weight	P/N
		ESR _{DC}	ESR _{AC} 1KHz				
(V)	(F)	(mΩ)	(mΩ)	(mA)	(mm)	(g)	-
3 (3.2)	1	400	260	0.010	8 x 14	0.8	SCCDER3R0105QRH080014E
	2	250	130	0.012	8 x 14	1	SCCDER3R0205QRH080014E
	3	150	80	0.014	8 x 20	1.4	SCCDER3R0305QRH080020E
	5	130	70	0.018	10 x 20	2.1	SCCDER3R0505QRH100020E
3R0	7	80	55	0.025	10 x 25	2.3	SCCDER3R0705QRH100025E
	10	60	40	0.040	10 x 30	3.2	SCCDER3R0106QRH100030E
	25	35	25	0.080	16 x 25	7	SCCDER3R0256QRH160025E
	50	22	15	0.150	18 x 40	12.8	SCCDER3R0506QRH180040E